Inter-Vehicular Communications: Quo vadis?

Onur Altintas Toyota InfoTechnology Center, Japan



TOYOTA InfoTechnology Center, Co. Ltd. Proprietary, All Rights Reserved

Traffic Accident Statistics



Vehicular communications is expected to remove up to 80% of the "unawareness" component



TOYOTA InfoTechnology Center, Co. Ltd. Proprietary, All Rights Reserved

- V2V communications as of today
 - Broadcast only
 - It is like yelling what you are doing whether it is of interest or not to people around you - 10 times/second
 - Receivers assess other vehicles' "threat levels"



- Reliability measure (Japan case)

- 80% correct reception at single attempt
- 96 % in two attempts

CENTER CO., LTD.

TOYOTA InfoTechnology Center, Co. Ltd. Proprietary, All Rights Reserved

Is it ready to deploy?

- Inclined to say "yes, almost ready" technically However,
- Non-mandated solutions must show immediate benefit in order to be accepted by the consumers
 - Seat belts \rightarrow Airbags \rightarrow IVC ?
 - Retrofit and aftermarket devices can accelerate deployment
- Ongoing challenges regarding privacy and security
 - Especially consumers in the US are very "privacyconscious"

Scalability



 CSMA/CA à la highway



TOYOTA InfoTechnology Center, Co. Ltd. Proprietary, All Rights Reserved

An unexpected role for vehicles

- Vehicles acting as part of "network" infrastructure
- Vehicles carrying "offloaded" data on behalf of infrastructure
 - Non-real time
 - Especially during disrupted/disconnected situations
- Implications for safety-critical vehicular applications need to be dealt carefully



What could be the next?

 If done correctly, V2V/V2I might be a key enabling technology towards autonomous automated driving





Automated Driving

- 360-degree, real time situational awareness required
- Number of radars, lidars, sensors, cameras in the vehicle increases
- Direct communication with other vehicles and with the infrastructure can significantly augment the sensing capability of a single vehicle
 - Not only the states of other vehicles, but also environmental information needs to be exchanged



Automated Driving

- Google's self-driving car gathers 750 megabytes of sensor data per second
 - Not all of that needs to be transmitted
 - But how much of it needs to be shared with neighboring vehicles ?
 - \rightarrow analysis of communications capacity needs



Credit: Google



- Cellular world is now moving to 5G
- Vehicular Communications is getting ready for 1G
- Deployment of the first generation of safety systems will happen soon
- We will only understand and acknowledge the problems by then
- Things will become more interesting for the research community towards the creation of the second and further generations of vehicular networking

